


EA series Inground light

EA series Inground light



Asymmetric Lighting




Precision Anti-glare



Full-aluminum Housing



Dual Breathing Valve





Unique Horseshoe-shaped Luminous Surface



EA-100-01/LED Inground light



Size:



EA-100-01/LED Inground light

Features:

- 1.Ultra-narrow frame and minimalist lamp body with design patent conforms to modern industrial aesthetics standard
- 2.Dual waterproof breathing valve design enhances heat dissipation performance and completely avoids the water mist problem
- 3. Anti-glare system adopts 0.2mm precision grid deflection 85°precision cutting light patent technology
- 4. Unique asymmetric lighting distribution design and horseshoe-shaped luminous surface presents the best light-emitting effect
- 5.Adopt die-casting aluminum lamp body and composite metal high efficiency heat dissipation patent technology


Parameter:

Fixture Parameter		LED Parameter	
Beam angle	10° 20° 30° 45° 60°	LED chip	Cree/OSRAM
Case material/color	Aluminum/Black	LED Item	XTE/3535
Cover material	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP67	LED Life	50000h
Fixture power	12W/15W	Other Parameter	
Input voltage	DC24V	Cable size	5 pins rubber cable(power cable 1.0 mm²,signal cable 0.3mm²)
Power factor	----	waterproof connector	IP67 waterproof terminal
Light efficiency	80lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel	Cable length	300mm
Light angle	Non-adjustable	Fixing clip	Plastic housing pre-buried
Cable location	From the bottom	Light distribution	
Series connection quantity	10pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	0.57kg		
Certification standards	GB7000.1-2015 GB7000.213-2008		


EA-140-01/LED Inground light



Size:



Unit (mm)



EA-140-01/LED Inground light

Features:

- 1.Ultra-narrow frame and minimalist lamp body with design patent conforms to modern industrial aesthetics standard
- 2.Dual waterproof breathing valve design enhances heat dissipation performance and completely avoids the water mist problem
- 3. Anti-glare system adopts 0.2mm precision grid deflection 85°precision cutting light patent technology
- 4. Unique asymmetric lighting distribution design and horseshoe-shaped luminous surface presents the best light-emitting effect
- 5.Adopt die-casting aluminum lamp body and composite metal high efficiency heat dissipation patent technology


Parameter:

Fixture Parameter		LED Parameter	
Beam angle	10° 20° 30° 45° 60°	LED chip	Cree/OSRAM
Case material/color	Aluminum/Black	LED Item	XTE/3535
Cover material	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP67	LED Life	50000h
Fixture power	18W/24W	Other Parameter	
Input voltage	DC24V/AC220V	Cable size	5 pins rubber cable(power cable 1.0 mm²,signal cable 0.3mm²)
Power factor	0.9	waterproof connector	IP67 waterproof terminal
Light efficiency	80lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel	Cable length	300mm
Light angle	Non-adjustable	Fixing clip	Plastic housing pre-buried
Cable location	From the bottom	Light distribution	
Series connection quantity	5pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	1.16kg		
Certification standards	GB7000.1-2015 GB7000.213-2008		


EA-180-01/LED Inground light



Size:



Unit (mm)



EA-180-01/LED Inground light

Features:

- 1.Ultra-narrow frame and minimalist lamp body with design patent conforms to modern industrial aesthetics standard
- 2.Dual waterproof breathing valve design enhances heat dissipation performance and completely avoids the water mist problem
- 3. Anti-glare system adopts 0.2mm precision grid deflection 85°precision cutting light patent technology
- 4. Unique asymmetric lighting distribution design and horseshoe-shaped luminous surface presents the best light-emitting effect
- 5.Adopt die-casting aluminum lamp body and composite metal high efficiency heat dissipation patent technology

Parameter:



Fixture Parameter		LED Parameter	
Beam angle	10° 20° 30° 45° 60°	LED chip	Cree/OSRAM
Case material/color	Aluminum/Black	LED Item	XTE/3535
Cover material	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP67	LED Life	50000h
Fixture power	36W/48W	Other Parameter	
Input voltage	DC24V/AC220V	Cable size	5 pins rubber cable(power cable 1.0 mm²,signal cable 0.3mm²)
Power factor	0.9	waterproof connector	IP67 waterproof terminal
Light efficiency	80lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel	Cable length	300mm
Light angle	Non-adjustable	Fixing clip	Plastic housing pre-buried
Cable location	From the bottom	Light distribution	
Series connection quantity	3pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	2.1kg		
Certification standards	GB7000.1-2015 GB7000.213-2008		

EA-220-01/LED Inground light



Size:

Unit (mm)



EA-220-01/LED Inground light

Features:

- 1.Ultra-narrow frame and minimalist lamp body with design patent conforms to modern industrial aesthetics standard
- 2.Dual waterproof breathing valve design enhances heat dissipation performance and completely avoids the water mist problem
- 3. Anti-glare system adopts 0.2mm precision grid deflection 85°precision cutting light patent technology
- 4. Unique asymmetric lighting distribution design and horseshoe-shaped luminous surface presents the best light-emitting effect
- 5.Adopt die-casting aluminum lamp body and composite metal high efficiency heat dissipation patent technology

Parameter:

Fixture Parameter		LED Parameter	
Beam angle	10° 20° 30° 45° 60°	LED chip	Cree/OSRAM
Case material/color	Aluminum/Black	LED Item	XTE/3535
Cover material	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP67	LED Life	50000h
Fixture power	54W/72W	Other Parameter	
Input voltage	DC24V/AC220V	Cable size	5 pins rubber cable(power cable 1.0 mm²,signal cable 0.3mm²)
Power factor	0.9	waterproof connector	IP67 waterproof terminal
Light efficiency	80lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel	Cable length	300mm
Light angle	Non-adjustable	Fixing clip	Plastic housing pre-buried
Cable location	From the bottom	Light distribution	
Series connection quantity	2pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	3.1kg		
Certification standards	GB7000.1-2015 GB7000.213-2008		