


XF series led wall washer

Throw away the visor for
double anti-glare

XF series led wall washer





Full structure waterproof + double anti-glare+ self-cleaning+13 patented technologies




XF-28-01/LED wall washer



Size:



Unit (mm)



XF-28-01/LED wall washer


Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Adopt the precise light distribution technology exclusive to wall washing lamp and 93% light transmittance ultra white toughened glass
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard

Parameter:



Fixture Parameter	LED Parameter		
Beam angle	20° 30° 40° 60°	LED chip	Lumileds/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	5050/2835
Cover material/color	Tempered glass	CCT	Single color/dual white/RGBW
P rate	P66 structure waterproof	LED Life	50000h
Fixture power	12W/15W	Other Parameter	
Input voltage	DC24V	Cable size	5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)
Power factor	----	waterproof connector	φ16mm Aluminium alloy
Light efficiency	75lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel, 4 pixels, 6 pixels, 8 pixels	Cable length	150mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Series connection quantity	10pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	1.2KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		

XF-28-A1/LED wall washer




0.2mm deviation 85° accurate cutting light direction

Size:



Unit (mm)



XF-28-A1/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Anti glare system adopts 0.2mm precision grid deflection 85° precision cutting light patent technology
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard



Parameter:

Fixture Parameter	LED Parameter		
Beam angle	20° 30° 40° 60°	LED chip	
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	
Cover material/color	Tempered glass	CCT	
IP rate	IP66 structure waterproof	LED Life	
Fixture power	12W/15W	Other Parameter	
Input voltage	DC24V	Cable size	
Power factor	----	waterproof connector	
Light efficiency	75lm/w(white)	connector	
Pixel segment	1 pixel, 4 pixels, 6 pixels, 8 pixels	Cable length	
Light angle	200° adjustable	Fixing clip	
Cable location	From the bottom	Light distribution	
Series connection quantity	10pcs		
Control way	ON-OFF/DMX512	-180 -150 -120 -90 -60 -30 0 30 60 90 120 150 180	
Environment temperature	-30°C~+35°C	光强(cd) COI:180,19.0° C90/270,20.0° 平均光束角(50%):19.5°	
Net weight	1.2KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		


XF-30-01/LED wall washer



Size:



Unit (mm)



XF-30-01/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Adopt the precise light distribution technology exclusive to wall washing lamp and 93% light transmittance ultra white toughened glass
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard


Parameter:

Fixture Parameter		LED Parameter	
Beam angle	20° 30° 40° 60°	LED chip	Cree/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	CLQ6B/3030
Cover material/color	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP66 structure waterproof	LED Life	50000h
Fixture power	18W/24W	Other Parameter	
Input voltage	DC24V	Cable size	5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)
Power factor	----	waterproof connector	φ16mm Aluminium alloy
Light efficiency	75lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel, 4 pixels	Cable length	150mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Series connection quantity	8pcs		
Control way	ON-OFF/DMX512	-180 -150 -120 -90 -60 -30 0 30 60 90 120 150 180	
Environment temperature	-30°C~+35°C	光强(cd) CO/180,19.0 CO/270,20.0 平均光束角(SD):19.5度	
Net weight	1.4KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		

XF-30-A1/LED wall washer



Size:



Unit (mm)

XF-30-A1/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Anti glare system adopts 0.2mm precision grid deflection 85° precision cutting light patent technology
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard



Parameter:

Fixture Parameter	LED Parameter		
Beam angle	20° 30° 40° 60°	LED chip Cree/OSRAM	
Case material/color	Aviation grade aluminum alloy(Grey) (Baitr Standard Grey or customized color)	LED Item CLQ6B/3030	
Cover material/color	Tempered glass	CCT Single color/dual white/RGBW	
IP rate	IP66 structure waterproof	LED Life 50000h	
Fixture power	18W/24W	Other Parameter	
Input voltage	DC24V	Cable size 5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)	
Power factor	----	waterproof connector φ16mm Aluminium alloy	
Light efficiency	75lm/w(white)	connector φ1.5mm Gold-plated solid Pins	
Pixel segment	1 pixel, 4 pixels	Cable length 150mm	
Light angle	200° adjustable	Fixing clip 304 Stainless steel	
Cable location	From the bottom	Light distribution	
Series connection quantity	8pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	1.4KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		


XF-38-01/LED wall washer



Size:



Unit (mm)



XF-38-01/LED wall washer


Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Adopt the precise light distribution technology exclusive to wall washing lamp and 93% light transmittance ultra white toughened glass
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard

Parameter:



Fixture Parameter		LED Parameter	
Beam angle	10° 20° 40° 60°	LED chip	Cree/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	XTE/CLQ6B/3030
Cover material/color	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP66 structure waterproof	LED Life	50000h
Fixture power	36W/48W	Other Parameter	
Input voltage	DC24V/AC85-265V	Cable size	5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)
Power factor	----	waterproof connector	Φ16mm Aluminium alloy
Light efficiency	75lm/w(white)	connector	Φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel, 4 pixels	Cable length	150mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Series connection quantity	4pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	1.8KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		

XF-38-A1/LED wall washer




0.2mm deviation 85° accurate cutting light direction

Size:



Unit (mm)



XF-38-A1/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Anti glare system adopts 0.2mm precision grid deflection 85° precision cutting light patent technology
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard


Parameter:

Fixture Parameter	LED Parameter		
Beam angle	10° 20° 40° 60°	LED chip	Cree/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	XTE/CLQ6B/3030
Cover material/color	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP66 structure waterproof	LED Life	50000h
Fixture power	36W/48W	Other Parameter	
Input voltage	DC24V/AC85-265V	Cable size	5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)
Power factor	----	waterproof connector	φ16mm Aluminium alloy
Light efficiency	75lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel, 4 pixels	Cable length	150mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Series connection quantity	4pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	1.8KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		


XF-50-01/LED wall washer



Size:



Unit (mm)




XF-50-01/LED wall washer


Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Adopt the precise light distribution technology exclusive to wall washing lamp and 93% light transmittance ultra white toughened glass
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard


Parameter:

Fixture Parameter		LED Parameter	
Beam angle	10° 20° 40° 60°	LED chip	Cree/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey) (Baitr Standard Grey or customized color)	LED Item	XTE/3535
Cover material/color	Tempered glass	CCT	Single color/dual white/RGBW
IP rate	IP66 structure waterproof	LED Life	50000h
Fixture power	54W/72W	Other Parameter	
Input voltage	DC24V/AC85-265V	Cable size	5 pins rubber cable(power cable 1.0 mm ² , signal cable 0.3mm ²)
Power factor	0.95	waterproof connector	φ16mm Aluminium alloy
Light efficiency	80lm/w(white)	connector	φ1.5mm Gold-plated solid Pins
Pixel segment	1 pixel, 4 pixels, 6 pixels, 8 pixels	Cable length	150mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Series connection quantity	2pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	2.2KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		


XF-50-A1/LED wall washer



Size:



Unit (mm)



XF-50-A1/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Anti glare system adopts 0.2mm precision grid deflection 85° precision cutting light patent technology
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard


Parameter:

Fixture Parameter	LED Parameter		
Beam angle	10° 20° 40° 60°	LED chip Cree/OSRAM	
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item XTE/3535	
Cover material/color	Tempered glass	CCT Single color/dual white/RGBW	
IP rate	IP66 structure waterproof	LED Life 50000h	
Fixture power	54W/72W	Other Parameter	
Input voltage	DC24V/AC85-265V	Cable size 5 pins rubber cable(power cable 1.0 mm², signal cable 0.3mm²)	
Power factor	0.95	waterproof connector φ16mm Aluminium alloy	
Light efficiency	80lm/w(white)	connector φ1.5mm Gold-plated solid Pins	
Pixel segment	1 pixel, 4 pixels, 6 pixels, 8 pixels	Cable length 150mm	
Light angle	200° adjustable	Fixing clip 304 Stainless steel	
Cable location	From the bottom	Light distribution	
Series connection quantity	2pcs		
Control way	ON-OFF/DMX512		
Environment temperature	-30°C~+35°C		
Net weight	2.2KG		
Certification standards	GB7000.1-2015 GB7000.201-2008		

XF-60-01/LED wall washer



Size:



Unit (mm)


XF-60-01/LED wall washer

Features:


1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Adopt the precise light distribution technology exclusive to wall washing lamp and 93% light transmittance ultra white toughened glass
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard

Parameter:

Fixture Parameter		LED Parameter	
Beam angle	6° 10° 20° 40° 60°	LED chip	Cree
Case material/color	Aviation grade aluminum alloy(Grey) (Bair Standard Grey or customized color)	LED Item	XTE
Cover material/color	Super White Glass	CCT	Single color
IP rate	IP66 structure waterproof	LED Power	5W
Fixture power	80W-100W	LED Life	50000h
Input voltage	AC85-265V	Other Parameter	
Power factor	0.9	Cable size	3 pins rubber cable
Light efficiency	85lm/w(white)	Cable length	300mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Control way	ON-OFF		
Environment temperature	-30°C~+35°C		
Net weight	3.8KG	Average light distribution graph (50%): 6.1度	
Certification standards	GB7000.1-2015 GB7000.201-2008		




XF-60-A1/LED wall washer



0.2mm deviation 85° accurate cutting light direction

Size:



Unit (mm)

XF-60-A1/LED wall washer

Features:

1. Minimalist lamp body with design patent conforms to modern industrial aesthetic standard
2. The whole structure waterproof adopts the new patented technology and technology of extrusion silicone strip
3. The sloped housing perfectly replaces the traditional design with visor and it is self-cleaning
4. Anti glare system adopts 0.2mm precision grid deflection 85° precision cutting light patent technology
5. 304 stainless steel with locking function damping rotating bracket with patented technology as standard

Parameter:

Fixture Parameter		LED Parameter	
Beam angle	6° 10° 20° 40° 60°	LED chip	Cree
Case material/color	Aviation grade aluminum alloy(Grey) (Baitr Standard Grey or customized color)	LED Item	XTE
Cover material/color	Super White Glass	CCT	Single color
IP rate	IP66 structure waterproof	LED Power	5W
Fixture power	80W-100W	LED Life	50000h
Input voltage	AC85-265V	Other Parameter	
Power factor	0.9	Cable size	3 pins rubber cable
Light efficiency	85lm/w(white)	Cable length	300mm
Light angle	200° adjustable	Fixing clip	304 Stainless steel
Cable location	From the bottom	Light distribution	
Control way	ON-OFF		
Environment temperature	-30°C~+35°C		
Net weight	3.8KG	Average luminous flux (50%): 6.1W	
Certification standards	GB7000.1-2015 GB7000.201-2008		

